



UE-095-NF

EDUCTOR 95 GPM 1.5" FEMALE X 1.5" MALE

Part No: UE-095-NF



Details

EDUCTOR 95 GPM 1.5" FEMALE X 1.5" MALE

Flow Rate	95 gpm (360 l/min)
Coupling Size Side A	1.5 inch (38mm)
Coupling Style Side A	Rocker
Coupling Swiveling/Rigid Side A	Swivel (full time, even after tightening)
Coupling Size Side B	1.5 inch (38mm)
Coupling Style Side B	Male Threads
Coupling Swiveling/Rigid Side B	Rigid
Pressure	200 psi (14 bar)

Related Videos

- [Eductors Video](#)

Online Technical Support Material

- [Eductor, In-Line Foam Eductor Manual](#)
- [Using Automatic Nozzles w/ Foam Eductors](#)

PRODUCT SERIES OVERVIEW

- Large, easy-to-change, and simple-to-read injection ratio metering head indicators allow for accurate mixing of Class A at ¼ and ½ %, and AFFF, or AFFF-AR foam concentrates at 1, 3, or 6%.
- The extra large 36" pickup hose and stainless steel wand are designed for use with all types of foams, including the thicker alcohol resistant concentrate -- which is easily and accurately picked up and injected into the water line.
- Unique push-button backflush feature allows for easy flushing of foam residue from the eductor, assuring functionality during the next operation.
- Quick Release Locker Ring allows eductor body to be detached from the metering head for easy storage.
- Designed for easy use with gloves.
- Maximum allowable back pressure is 130 psi (9 Bar).