



H-2BLITZ

HANDLINE PLAYPIPE 2.5" NH (65mm)

Part No: H-2BLITZ



Flow Control Method	Automatic (constant pressure, variable flow, constant gallonage, flow does not change with pattern)
Flow Rate	95-300 gpm (360-1150 l/min)
Coupling Size (Nozzles)	2.5 inch (65mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Pressure	100 psi (7bar)
Nozzle Body Style	Nozzle with shutoff and playpipe grip
Valve Design	Slide Valve (Stainless)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Fog Pattern Method	Molded Rubber Teeth (fixed)
Nozzle Bumper Material	Rubber - bonded
Certifications	N/A

Details

HANDLINE PLAYPIPE 2.5" NH (65mm)

Smallest, most compact nozzle/playpipe combination available for use on 2.5" (65mm) or 3" (75mm) lines. Automatic 100 psi (7 bar) pressure control with a flow capacity of 95-300 gpm (360-1150 l/min). Includes pressure-assisted flush without shutting down, patented slide-type valve for turbulence-free flow control, six detent flow positions, molded rubber teeth for full-fill "power fog" pattern, and "Gasket Grabber" inlet screen. Lightweight hardcoat anodized aluminum materials for maximum resistance to corrosion and wear. Nozzle is attached to valve and is not removable. Rubber coated handles are designed to reduce fatigue. 2.5" NH (65mm) rocker lug full-time swivel coupling is standard.

Related Videos

- [Handline Upgrade for Nozzles](#)
- [How to Adjust a TFT Slide Valve](#)
- [Handline Series](#)

Online Technical Support Material

- [Handline Demo Sheet](#)
- [Handline Flow & Reaction Chart](#)
- [Handline Product Brochure](#)
- [Handheld Automatic Nozzle Instructions](#)
- [Handline Upgrade Instructions](#)
- [Handline Nozzles Manufactured After 12/1/2003](#)

PRODUCT SERIES OVERVIEW

- The full size Handline nozzle incorporates TFT's unique stainless steel slide valve for turbulence free flow control and includes the exclusive integrated debris screen to prevent stream quality degradation. All models accept low and multi-expansion foam attachments for increased finished foam performance.

- The full size Handline nozzle is available with 100, 75, or 55 psi operational pressure to meet any fire ground operational challenge. The high strength bonded rubber fog teeth provide a full filled pattern that pushes heat flame and smoke ahead and away from the firefighting team.

- The full size Handline nozzle comes standard with reflective labeling as well as your choice of color coded pistol grip and shut off handle. This constant pressure variable gallonage nozzle series is available in tip only, shut off, and playpipe configurations, is individually serialized, and comes with TFT's exclusive 5 year warranty.