



HD-VPGI

DUAL-FORCE W/GRIP 1.5" NH (38mm)

Part No: HD-VPGI



Details

DUAL-FORCE W/GRIP 1.5" NH (38mm)
Automatic pressure control with a flow capacity of 95-300 gpm (360-1150 l/min). Includes pressure-assisted flush without shutting down, patented slide-type valve for turbulence-free operator flow control, six detent flow positions, molded rubber teeth for full-fill "power fog", and "Gasket Grabber" inlet screen. Pistol grip is mounted below the valve (HD-VPGI), or behind the valve (HD-VPG). Lightweight hardcoat anodized materials for maximum resistance to corrosion and wear. 1.5" NH (38mm) rocker lug full-time swivel coupling is standard. Nozzle may be switched between standard 100 psi (7 bar) and low pressure.

Flow Control Method	Automatic (constant pressure, variable flow, constant gallonage, flow does not change with pattern)
Flow Rate	95-300 gpm (360-1150 l/min)
Coupling Size (Nozzles)	1.5 inch (38mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Pressure	55 & 100 psi (3 & 7 bar)
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Slide Valve (Stainless)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Fog Pattern Method	Molded Rubber Teeth (fixed)
Nozzle Bumper Material	Rubber - bonded
Certifications	N/A

Related Videos

- [Dual Pressure Knob Replacement](#)
- [Pistol Grip Replacement](#)
- [How to Adjust a TFT Slide Valve](#)
- [Dual Force Series](#)

Online Technical Support Material

- [Dual-Force \(low pressure\) Flow & Reaction Chart](#)
- [Dual-Force Flow & Reaction Chart](#)
- [Dual-Force Highrise Packs/Break/Extend Procedures](#)
- [Service Poster - Dual Force Nozzles](#)
- [Handline Nozzles Manufactured After 12/1/2003](#)

PRODUCT SERIES OVERVIEW

- The full size Dual Force Handline nozzle incorporates TFT's unique stainless steel slide valve for turbulence free flow control and includes the exclusive integrated debris screen to prevent stream quality degradation. All models accept low and multi-expansion foam attachments for increased finished foam performance.
- The full size Dual Force Handline nozzle is available with 100/55psi or 75/45psi operational pressure choices to meet any fire ground operational challenge. The high strength bonded rubber fog teeth provide a full filled pattern that pushes heat flame and smoke ahead and away from the firefighting team.
- The full size Dual Force Handline nozzle comes standard with reflective labeling as well as your choice of color coded pistol grip and shut off handle. This dual pressure variable gallonage nozzle series is available in tip only, shut off, and playpipe configurations, is individually serialized, and comes with TFT's exclusive 5 year warranty.