



HML-VPGI

LOW PRESSURE 75 PSI VERSION

Part No: HML-VPGI



Details

LOW PRESSURE 75 PSI VERSION

Same as HM-VPGI above, but operates at a lower pressure of approximately 75 psi (5 bar). Flow range is 70-200 gpm (260-760 l/min).

Flow Control Method	Automatic (constant pressure, variable flow, constant gallonage, flow does not change with pattern)
Flow Rate	70-200 gpm (260-760 l/min)
Coupling Size (Nozzles)	1.5 inch (38mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Pressure	75 psi (5bar)
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Slide Valve (Stainless)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Fog Pattern Method	Molded Rubber Teeth (fixed)
Nozzle Bumper Material	Rubber - bonded
Certifications	NFPA/FM

Related Videos

- [Mid-Matic/Mid-Force](#)
- [Pistol Grip Replacement](#)
- [Mid-Matic Series](#)

Online Technical Support Material

- [Mid-Force & Mid-Matic Colored Handles](#)
- [Mid-Matic Flow & Reaction Chart](#)
- [Mid-Matic/Mid-Force Brochure](#)
- [Mid-Matic Automatic Nozzle NFPA 1964 Compliance](#)
- [Handheld Automatic Nozzle Instructions](#)
- [Mid-Matic FM Approval](#)
- [Service Procedure: Mid-Matic, Mid-Force, Metro 1](#)

PRODUCT SERIES OVERVIEW

- The Mid-Matic handline nozzle incorporates TFT's unique stainless steel slide valve for turbulence free flow control and includes the exclusive integrated debris screen to prevent stream quality degradation. All models accept low and multi-expansion foam attachments for increased finished foam performance.
- The Mid-Matic handline nozzle is available with 100, 75 or 55psi operational pressure choices to meet any fire ground operational challenge. All models are available with your choice of high strength bonded rubber fog teeth which provide a full filled pattern, or the wide protective pattern of TFT's unique stainless steel spinning teeth design.
- The Mid-Matic handline nozzle comes standard with reflective labeling as well as your choice of color coded pistol grip and shut off handle. This constant pressure variable gallonage nozzle series is available in tip only and shut off configurations, is individually serialized, and comes with TFT's exclusive 5 year warranty.