



HL-TO

HANDLINE TIP LOW PRESSURE VERSION

Part No: HL-TO



Details

HANDLINE TIP LOW PRESSURE VERSION
Same as H-TO above, but operates at a low pressure of approximately 75 psi (5 bar). Flow range 95-250 gpm (360-950 l/min).

Flow Control Method	Automatic (constant pressure, variable flow, constant gallonage, flow does not change with pattern)
Flow Rate	95-250 gpm (360-950 l/min)
Coupling Size (Nozzles)	1.5 inch (38mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Rigid
Pressure	75 psi (5bar)
Nozzle Body Style	Tip with no shutoff
Valve Design	No Valve
Valve Actuation Method	No Actuation Method
Fog Pattern Method	Molded Rubber Teeth (fixed)
Nozzle Bumper Material	Rubber - bonded
Certifications	N/A

Related Videos

- [Handline Upgrade for Nozzles](#)
- [How to Adjust a TFT Slide Valve](#)
- [Handline Series](#)

Online Technical Support Material

- [Handline Demo Sheet](#)
- [Handline Flow & Reaction Chart](#)
- [Handline Product Brochure](#)
- [Handheld Automatic Nozzle Instructions](#)
- [Handline Upgrade Instructions](#)
- [Handline Nozzles Manufactured After 12/1/2003](#)

PRODUCT SERIES OVERVIEW

- The full size Handline nozzle incorporates TFT's unique stainless steel slide valve for turbulence free flow control and includes the exclusive integrated debris screen to prevent stream quality degradation. All models accept low and multi-expansion foam attachments for increased finished foam performance.
- The full size Handline nozzle is available with 100, 75, or 55 psi operational pressure to meet any fire ground operational challenge. The high strength bonded rubber fog teeth provide a full filled pattern that pushes heat flame and smoke ahead and away from the firefighting team.
- The full size Handline nozzle comes standard with reflective labeling as well as your choice of color coded pistol grip and shut off handle. This constant pressure variable gallonage nozzle series is available in tip only, shut off, and playpipe configurations, is individually serialized, and comes with TFT's exclusive 5 year warranty.