


AIRGUN 40

AIRGUN 40...

A 600 blow per minute, 7 pound pneumatic impact tool. Combining ease of handling, very low air consumption and high power output, it is an ideal tool for rescue work.

Vehicle crash sites, metal clad buildings, aircraft penetration, exhaust ducts and composite structural material are typical barriers often faced by rescue personnel. The Airgun 40, using one of several specially designed tool bits, should be your tool of choice when faced by these situations. The Airgun 40 is also an ideal confined space tool.



AIRGUN 40 KIT



TECHNICAL DATA

Length (without bit)	21.2 in (53.9 cm)
Width	6.1 in (15.5 cm)
Thickness	1.9 in (4.8 cm)
Weight (Airgun without bit)	7 Lbs (3.2 kg)
Air Pressure Range	40-200 PSI (2.8-13.8 Bar)
Air Consumption at 100 PSI	5.2 CFM (147.3 L/min)
Blows/Minute (approx.)	600 - 720
Power Output @ 200 PSI	40 lbf • ft (5.5 N • m)
Power Output @ 50 PSI	6 lbf • ft (.83 N • m)
Kit Weight	31 Lbs (14.1 kg)
Kit Dimensions	24 in long (61.0 cm) 11 in wide (27.9 cm) 12 in high (30.5 cm)
Shank Size	.4 in (1.0 cm)

ORDERING INFORMATION

22-550005	KIT, Airgun 40, consisting of the following:
22-550000	Airgun 40, with Inline Oiler
22-895400	Pressure Regulator 6000-300 PSI (413.7-20.7 Bar)
22-890520	Air Hose, 3/8 in (9.5 mm) dia. X 32ft (9.8 m) Yellow
22-550252	Bit, 10 in (25.4 cm) Curved metal cutter
22-550262	Bit, 11 in (27.9 cm) Bullpoint
22-550264	Bit, 11 in (27.9 cm) Chisel, 3/4 in (1.9 cm) wide
22-550291	Oil, lubricating, 4 oz. (113 g)
22-550259	Tool, retainer service
22-550094	Hex key 7/32 in (0.6 cm)
22-550099	Hex Key 3/16 in (0.5 cm)
22-550095	Manual, Operating and Instruction
22-700235	Goggles, plastic safety
22-550370	Ballistic Nylon Carrying Case 23 X 10 1/4 X 13 in (58.4 X 26.0 X 33.0 cm)

OPTIONAL TOOL BITS

22-550240	Bit, 6 in (15.2 cm) Piercing Applicator 1 in (2.5 cm) O.D. X 1/2 in (1.3 cm) I.D.
22-550244	Driver for Neoprene Plug
22-550246	Neoprene Plug 4 in (10.2 cm) LG 3/4-1.5 in (1.9-3.8 cm) dia
22-550250	Bit, 14 in (35.6 cm) Piercing Applicator 1 in (2.5 cm) O.D. X 3/4 in (1.9 cm) I.D.
22-550254	Bit, 10 in (25.4 cm) Dual Cutter
22-550256	Bit, 11 in (27.9 cm) Dual Cutter with Bullpoint
22-550258	Bit, 10 in (25.4 cm) Lock Breaker
22-550260	Bit, 10 in (25.4 cm) Heavy Duty Metal Cutter 0.5 in (1.3 cm) Depth of Cut
22-550263	Bit, 16 in (40.6 cm) Bullpoint
22-550265	Bit, 16 in (40.6 cm) Chisel 3/4 in (1.9 cm) wide
22-550274	Bit, 20 in (50.8 cm) Spade 3 in (7.6 cm) wide
22-550270	Bit, Deep 1.1 in (2.8 cm) Panel Cutter for Metals
22-550272	Bit, Deep 1.2 in (3.1 cm) Panel Cutter with Relief for Aircraft Windows

Paratech Incorporated

P.O. Box 1000, Frankfort, IL 60423 USA
Customer Service: 800.435.9358
Phone: 815.469.3911 Fax: 815.469.7748
www.paratech.us E-mail: paratech@paratech.us

Paratech Europe, Branch of Paratech Inc.

P.O. Box 174, 5260 Odense S, Denmark
Phone: +45.66.11.24.22 Fax: +45.66.11.24.32
Customer Service: 800.435.9358
www.paratech.us Email: paratech@paratech.dk

