



## D1040BC

### BUBBLE CUP TIP 1" NH (25mm)

Part No: **D1040BC**



#### Details

##### BUBBLE CUP TIP 1" NH (25mm)

Dual gallonage Bubble Cup nozzle with two flow settings of 10 and 40 gpm@ 100 psi (37 and 150 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. This tip only design has a twist "off" position for break-and-extend operations. 1" NH (25mm) rigid thread is standard.

Flow Control Method	Selectable Flow at a pressure (flow changes with pattern)
Flow Rate	10 & 40 gpm (37 & 150 l/min)
Coupling Size (Nozzles)	1.0 inch (25mm)
Coupling Style (Nozzles)	Knurled (Diamond pattern)
Coupling Swiveling/Rigid (Nozzles)	Rigid
Pressure	100 psi (7bar)
Nozzle Body Style	Tip with shutoff
Valve Design	Twist Style (baffle shutoff)
Valve Actuation Method	Rotational
Fog Pattern Method	no teeth
Nozzle Bumper Material	PVC
Certifications	N/A
Foam Expansion Performance	Low Expansion

#### Related Videos

- [Bail Handle and Valve Seat Ball Valve](#)
- [Foam Concentrate Video](#)
- [Foam Overview Video](#)
- [BubbleCup and QuadraCup Series Video](#)

#### Online Technical Support Material

- [BubbleCup & Twister Instruction Manual](#)
- [BubbleCup & Twister Operation & Maintenance Manual](#)
- [Service Procedure: 1.0" Twister and 1.0" BubbleCup](#)
- [Service Procedure: 1.5" Twister and 1.5" BubbleCup](#)
- [Twister and BubbleCup Nozzles](#)