



ME1-VPGI

METRO 1 W/GRIP1.5" NH (38mm)

Part No: ME1-VPGI



Details

METRO 1 W/GRIP1.5" NH (38mm)
Fixed gallonage nozzle with 14 flow and pressure choices. Includes flush without shutting down, patented slide-type valve for turbulence-free flow control, six detent flow positions, and "Gasket Grabber" inlet screen. Lightweight hardcoat anodized aluminum for maximum resistance to corrosion and wear. Pistol grip is mounted below the valve. 1.5" NH (38mm) full-time swivel rocker lug coupling is standard.

Flow Control Method	Fixed Flow at a pressure (constant gallonage, flow does not change with pattern)
Flow Rate	Metro 1 - User Selectable
Coupling Size (Nozzles)	1.5 inch (38mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Pressure	Metro - User Selectable
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Slide Valve (Stainless)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Fog Pattern Method	Molded Rubber Teeth (fixed)
Nozzle Bumper Material	Rubber - bonded
Certifications	NPFA
Foam Expansion Performance	N/A

Related Videos

- [Pistol Grip Replacement](#)
- [How to Adjust a TFT Slide Valve](#)
- [Metro Series Video](#)

Online Technical Support Material

- [Metro 1 & Metro 2 Instruction Manual](#)
- [Metro Demo Sheet](#)
- [Metro Fixed Gallonage Nozzle NFPA 1964 Compliance](#)
- [Service Procedure: Mid-Matic, Mid-Force, Metro 1](#)
- [Service Procedure: 1.5 QuadraFog & QuadraCup](#)