



ME1-V

METRO 1 NOZZLE 1.5" NH (38mm)

Part No: ME1-V



Flow Control Method	Fixed Flow at a pressure (constant gallonage, flow does not change with pattern)
Flow Rate	Metro 1 - User Selectable
Coupling Size (Nozzles)	1.5 inch (38mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Pressure	Metro - User Selectable
Nozzle Body Style	Nozzle with shutoff
Valve Design	Slide Valve (Stainless)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Fog Pattern Method	Molded Rubber Teeth (fixed)
Nozzle Bumper Material	Rubber - bonded
Certifications	NPFA
Foam Expansion Performance	N/A

Details

METRO 1 NOZZLE 1.5" NH (38mm)
Fixed gallonage nozzle with 14 flow and pressure choices. Includes flush without shutting down, patented slide-type valve for turbulence-free flow control, six detent flow positions, and "Gasket Grabber" inlet screen. Lightweight hardcoat anodized aluminum for maximum resistance to corrosion and wear. 1.5" NH (38mm) full-time swivel rocker lug coupling is standard.

Related Videos

- [How to Adjust a TFT Slide Valve](#)
- [Metro Series Video](#)

Online Technical Support Material

- [Metro 1 & Metro 2 Instruction Manual](#)
- [Metro Demo Sheet](#)
- [Metro Fixed Gallonage Nozzle NFPA 1964 Compliance](#)
- [Service Procedure: Mid-Matic, Mid-Force, Metro 1](#)
- [Service Procedure: 1.5 QuadraFog & QuadraCup](#)